

VISONG TEST's Constant Current Power 61000 series are signal conditionings for dynamic measurements with ICP® compatible transducers.



Specifications:

Model	Unit	61000	61001	61011	61012		
Channel	.	1	1	4	8		
Gain	.	x1	x1	x1,x10	x1,x10		
Output Voltage	V	24					
Constant Current	mA	2~10 (can be user adjustable)					
Frequency Range	Hz	0.025~100k					
Working Status Indicator	.	LED/ammeter	-	LED/ammeter	LED/ammeter		
Broadband Noise	μ Vrms	15					
Battery Power	.	9Vx1	-	9Vx3x2	9Vx3x3		
External DC Power Supply	V	DC7~30	DC18~30	220V/DC18~30	220V/DC18~30		
Input/Output Connector	.	BNC					
Size	mm	91x61x27	ϕ 15x50	290x200x50	483x250x50		
Weight	gram	32	30	2800	4850		

VISONG TEST's 62200/62300 one-channel Charge Amplifier features:

- Portable and convenient design
- Charge / Voltage switch with working status indicator and without pre-setting
- Both 9V battery and external DC power



Specifications:

Model	Unit	62200	62300
Channel	.	1	1
Input	pC	±5000	±500
Output	V	±5	
Sensitivity	mV/pC	1	10
Frequency Range	Hz	0.3~6000	
Power Supply	.	DC7~30V or 9V battery	
Broadband Noise	mVrms	≤8 x10 ⁻³	≤80x10 ⁻²
Size	mm	91x61x27	91x61x27